

Model	SI-0007	SI-0008	SI-0009	SI-0010
Type	IP Camera Bullet Fixed View			
General Information				
Resolution	4 MP			
Sensor	CMOS & Goke			
Lens	3.6 mm			
Angle Adjustment	0-360° pan, 0-90° tilt, 0-360° swivel			
Main Stream	20FPS (2560×1440), 25FPS (2304×1296, 1920×1080, 1280×720)			
Sub Stream	22FPS (D1), 25FPS (HD1, CIF, QVGA)			
Compression	H.265+/H.265/H.264 video encode, Support Bitrate 0.1M~8Mbps; Support Frame rate 1~30 Fps/s			
WDR	120dB WDR			
Image Enhance	BLC, HLC, 2D/3D DNR			
Image Settings	Rotate, Mirror, Privacy Mask, Saturation, Brightness, Contrast, Sharpness, Gain, White Balance adjustable by software or web browser			
Min. illumination	0.01 lux / 0 Lux with LED on			
Light	4 × IR	4 x Warmlights		
Light range	30 m			
Field of view	H: 77.7°; V: 47.3°; D: 87.5°			
Analytics	Motion, human-shape, face snapshot, Alarms (Intrusion, Camera Cover, etc...)			
Mic / speaker	Built-in mic, one-way audio (SI-001, SI-0003), two way audio (SI-0002, SI-0004) G.711-u/G.711-a			
Card Slot	Not Available			
Communications				
Interface	PoE (802.3af) / RJ45			
Protocol	HTTP/RTSP/DHCP/NTP/ONVIF/P2P			
Mechanical Information				
Housing	Metal			
Protection Rate	IP67			
Working Temperature	-40° ... 60° C			
Allowed Humidity	0 ... 95% (non-condensing)			
Size	68 mm (W) * 68 mm (H) * 175 mm (L)			